

10478 Ridge Road • Medina, New York 14103 Phone: 585-735-9668 • Toll Free: 888-290-9522 Fax: 585-735-9965 • www.virtualpolymercompounds.com

Administrative Office: One John James Audubon Pkwy • Amherst, NY 14228

## Typical Options Parshall Flumes

- Staff Gauge (Available in various widths and markings including flow data)
- **Stilling Well** (Integral or remote, 6", 8", 10", or 12" ID, with or without plug)
- ▶ **Bubbler Tube** (Stainless Steel, ¼" ID, Integral to Flume)
- Sampler Tube (Stainless Steel, 3/8" ID, Integral to Flume)
- Inlet and Outlet End Connection (Integral or Removable)
- ▶ Pipe Connection (Neoprene Boot or ANSI Pipe Flange Connection)
- Special Chemical Resistant Fabrication (pH Range of 1 to 14)
- Ultrasonic Transducer Bracket (Fixed at 14" or 24" or Adjustable)
- pH Sensor Cavity (Fabricated to fit most sensors)
- Wing Walls and Bulk Heads (Custom Fabricated to meet job requirements)
- Nesting Options (Standard or Special Designs)
- Energy Absorption Racks (Fixed or Removable)
- Standard or Special Depths (Including surge boxes)
- Enclosed Flumes (For odor control)
- Flume Covers (Grating, Fiber Sheeting, Clear Polycarbonate)
- Montana Cut Design (Available in all standard sizes)
- Special Design (Will meet your special project needs)