



**NOTE**

- 1) EXTERIOR COLOR—OFF WHITE
- 2) INTERIOR COLOR—OFF WHITE
- 3) SHELTER CONSTRUCTED USING A CLASS I FIRE RESISTANT RESIN,FLAME SPREAD <25
- 4) PANELS CONSTRUCTED WITH A NOMINAL 1/8" CHOPPED GLASS LAMINATE
- 5) FLOORING CONSTRUCTED WITH 3/4 PLYWOOD WITH SIDES AND BOTTOM PROTECTED  
INTERIOR FLOOR TO BE GRAY COLORED SLIP RESISTANT
- 6) UNIT SHIPPED PREASSEMBLED AND PREWIRED PER N.E.C. CODES
- 7) SHELTER MEETS OR EXCEEDS THE VALUES LISTED
 

WIND PRESSURE EQUAL TO 110 MPH	27 PSF
LIVE LOAD ON FLOORING	50 PSF
SNOW LOAD	40 PSF
DEAD LOAD	40 PSF
WIND UPLIFT LOAD	27 PSF

**VIRTUAL POLYMER COMPOUNDS, LLC**

10478 RIDGE ROAD, MEDINA, NEW YORK 14103  
TOLL FREE: 800-636-5255 PHONE: 585-735-9668 FAX:585-735-9965

TITLE: **ECOTECH MODEL# SNET35**

SCALE: 1/32

DATE:

DWG. NO.:

**SNET35**