

INTRODUCING MODEL WBF

FIBERGLASS WALL BOX FAN

ABOUT CFT

COMPOSITE FAN TECHNOLOGY MANUFACTURES A COMPLETE LINE OF FIBERGLASS FANS. CFT FANS ARE DESIGNED TO ACHIEVE MAXIMUM CORROSION RESISTANCE WHILE OFFERING RUGGED CONSTRUCTION, EASE OF MAINTENANCE AND EFFICIENT OPERATION.



STANDARD FEATURES:

- 13 SIZES AVAILABLE (12" TO 60" DIAMETER)
- CAPACITIES UP TO 90,000 CFM
- PRESSURES UP TO 2" W.G.
- SOLID FIBERGLASS HOUSING AND HIGHLY EFFICIENT BACKWARD CURVED IMPELLER CONSTRUCTED OUT OF PREMIUM CORROSION RESISTANT VINYL ESTER RESIN
- ALL RESIN IS FIRE RETARDANT WITH A CLASS 1 FLAME SPREAD OF 25 OR LESS PER ASTM E-84
- STANDARD HOUSING COLOR IS GRAY
- ALL EXTERIOR SURFACES CONTAIN UV INHIBITOR
- C-GLASS SURFACE VEIL ON AIRSTREAM SURFACES
- 316 SST SHAFT (BELT DRIVE ONLY) AND HARDWARE
- FLANGED FIBERGLASS WALL SLEEVE
- FIBERGLASS MOTOR MOUNT
- TEFC MOTOR (1/3 HP MINIMUM)

OPTIONAL ACCESSORIES

FRP DAMPER, STATIC GROUNDING OF AIRSTREAM, DISCONNECT SWITCHES, INLET/OUTLET GUARDS, FRP WEATHER HOOD, CUSTOM COLORS, SYNTHETIC SURFACE VEIL, AND CUSTOM RESIN FORMULATIONS ARE AVAILABLE.

